

Safari Equinox I

A versitile, compact glamping solution.

Easily transportable and and simply setup, the 13.2m² (142ft²) Safari Equinox I is a great base of operations for the avid adventurer. Made from lightweight materials and engineered to be compact, the Equinox I is highly durable and weather-resistant ensuring resilience against a variety of tough weather conditions. Utilizing premium, eco-conscious materials, Luna's Equinox series endevours to reduce environmental impact while prioritizing sustainability.

Leaders in frame strength and durability



Etched aluminum framework and steel connectors




Fully adjustable anti-slip buckles




Reinforcement tightening



Rachet strap tensioners





SPECIFICATIONS

Outer Dimension	3.5m x 4.2m x 2.8m
WxLxH	(11.5ft x 13.8ft x 9.2ft)
Outer Area	14.7m² (158.2ft²)
Platform Size	3.6m x 4.8m
WxL	(11.8ft x 15.8ft)
Inner Dimension	3.3m x 4m x 2.6m
WxLxH	(10.8ft x 13.1ft x 8.5ft)
Inner Area	13.2m² (142.0ft²)
Max Wind Load	130km/h (80mph)
-to increase wind load ratin	ng please contact.

Package size 4m x 1m x 0.5m (2m3) WxLxH 13ft x 3.3ft x 1.6ft (70.6ft³)

Package weight 200kg (441lbs)

MATERIALS

Roof Fabric 750 g/m² double-coated opaque PVC (beige), waterproof, UV resistant, flame retardant B1.

Inner Lining 370 g/m2 Canvas, including 1.2m x 0.8m window w/ mosquito net and zipper door; waterproof; mildew-resistant; fire retardant.

Insulation (optional add-on) 1 or 2 layer aluminum foil bubble insulation + canvas fabric. Radiation heat reflection coefficient 85%, waterproof, fire retardant.

Window size 1.9m x 1.1m (6.2ft x 3.6ft) Windows per tent

Ground Lining 480 g/m² beige PVC.

Framework 6063-T6 aluminum alloy, 70mm dia, 1.5mm thickness, wood pattern.

Connector 76mm x 2mm black Q235B steel.

Netting 40gsm white. Rope 6mm nylon ropes.

Stakes 5mm steel.













