

Safari Equinox II

True harmony of size and utility.

Crafted from superior, weather-resistant aluminum and fabric, The Safari Equinox II can withstand winds exceeding 130 kilometers per hour. Its modular design facilitates effortless repairs and part replacements which ultimately translates into better value and a longer lasting, more robust product lifespan of 3-5 years—twice the longevity of the typical tent. Furthermore, customizable amenities such as built-in sunshades and cushioned flooring promise comfort across diverse outdoor settings.

Leaders in frame strength and durability



Etched aluminum framework and steel connectors




Fully adjustable anti-slip buckles




Automoble-grade baking metal finish



Rachet strap tensioners





SPECIFICATIONS

Outer Dimension	3.5m x 5.0m x 3.3m
WxLxH	(11.5ft x 16.4ft x 10.8ft)
Outer Area	17.5m² (188.3ft²)
Platform Size	3.6m x 5.6m
WxL	(11.8ft x 18.4ft)
Inner Dimension	3.3m x 3.3m x 3.1m
WxLxH	(10.8ft x 10.8ft x 10.2ft)
Inner Area	10.9m² (117.3ft²)

Max Wind Load 130km/h (80mph) -to increase wind load rating please contact.

Package size 4m x 1m x 0.6m (2.4m³) WxLxH 13ft x 3.3ft x2ft (85.0ft³)

Package weight 250kg (551lbs)

MATERIALS

Roof Fabric 750 g/m² double-coated opaque PVC (beige), waterproof, UV resistant, flame retardant B1.

Inner Lining 370 g/m2 Canvas, including 1.2m x 0.8m window w/ mosquito net and zipper door; waterproof; mildew-resistant; fire retardant.

Insulation (optional add-on) 1 or 2 layer aluminum foil bubble insulation + canvas fabric. Radiation heat reflection coefficient 85%, waterproof, fire retardant.

Window size 1.17m x 0.8m (3.8ft x 2.6ft)
Windows per tent 1 Rear

Ground Lining 480 g/m² beige PVC.

Framework 6063-T6 aluminum alloy, 70mm dia, 1.5mm thickness, wood pattern.

Connector 76mm x 2mm black Q235B steel.

Netting 40gsm white.

Rope 6mm nylon ropes.

Stakes 5mm steel.











RUGGED

COZV

DLIDABLE

SAFE

ENGINEERED

